

1. Identification

Product identifier C34™ Cement Powder Component

Other means of identification
SDS number 4303

Recommended use Bonding of Carbon and Graphite.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier GrafTech International Holdings Inc. or affiliate
982 Keynote Circle
Brooklyn Heights, Ohio 44131
+1 216-676-2555

Contact person Product Responsibility Manager +1-216-676-2304

E-mail sds@graftech.com

Emergency telephone number For Chemical Emergency ONLY, call CHEMTREC at:
+1-800-424-9300 or +1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1
Carcinogenicity Category 2
Specific target organ toxicity, repeated exposure Category 2 (Lungs)

OSHA defined hazards Combustible dust

Label elements



Signal word Warning

Hazard statement May form combustible dust concentrations in air. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs (Lungs) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Prevent dust accumulation to minimize explosion hazard. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Do not breathe dust. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Observe good industrial hygiene practices.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Graphite	7782-42-5	< 60
Carbon black	1333-86-4	< 25
Phenolic resin	9003-35-4	< 20
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	< 3
Methenamine	100-97-0	< 2

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes. Coughing. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). Apply extinguishing media carefully to avoid creating airborne dust. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Minimize dust generation and accumulation. Collect dust using a vacuum cleaner equipped with HEPA filter. This product is miscible in water. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
Graphite (CAS 7782-42-5)	PEL	2000 mg/m3 500 ppm 5 mg/m3 15 mg/m3	Respirable fraction. Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Graphite (CAS 7782-42-5)	TWA	15 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m ³	
	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m ³	Respirable.
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. Provide explosion-proof ventilation for high dust concentrations.		
Individual protection measures, such as personal protective equipment			
Eye/face protection	Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves.		
Skin protection			
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.		
9. Physical and chemical properties			
Appearance	Black powder.		
Physical state	Solid.		
Form	Powder.		
Color	Black.		
Odor	Phenol.		
Odor threshold	Not available.		
pH	Not applicable.		
Melting point/freezing point	No data available.		
Initial boiling point and boiling range	Not applicable.		
Flash point	Not applicable.		
Evaporation rate	Not applicable.		
Flammability (solid, gas)	Dust may form explosive mixture with air.		
Upper/lower flammability or explosive limits			
Flammability limit - lower (%)	Not applicable.		
Flammability limit - upper (%)	Not applicable.		
Explosive limit - lower (%)	Not available.		
Explosive limit - upper (%)	Not available.		
Vapor pressure	Not applicable.		

Vapor density	Not applicable.
Relative density	1
Solubility(ies)	
Solubility (water)	0.1 - 1 Slightly soluble.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	No data available.
Viscosity	Not available.
Other information	
Bulk density	Not applicable.
Explosive properties	Dust may form explosive mixture with air.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials. Minimize dust generation and accumulation.
Incompatible materials	Strong oxidizing agents. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system.
Skin contact	Dust or powder may irritate the skin. May cause an allergic skin reaction.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Carbon black (CAS 1333-86-4)		
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Oral		
LD50	Rat	> 8000 mg/kg
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)		
Acute		
Inhalation		
LD50	Rat	2.81 mg/l
Graphite (CAS 7782-42-5)		
Acute		
Oral		
LD50	Rat	> 10000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	3 Not classifiable as to carcinogenicity to humans.
NTP Report on Carcinogens	Not listed.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not regulated.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs (Lungs) through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Carbon black (CAS 1333-86-4)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Leuciscus idus >= 1000 mg/l, 96 Hours
Methenamine (CAS 100-97-0)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 29868 - 43390 mg/l, 48 hours
Fish	LC50	Bleak (Alburnus alburnus) > 10000 mg/l, 96 hours

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	The product is slightly soluble in water.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Additional information is given in the Safety Data Sheet.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Carbon black (CAS 1333-86-4)

US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Graphite (CAS 7782-42-5)

US. New Jersey Worker and Community Right-to-Know Act

Carbon black (CAS 1333-86-4)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Graphite (CAS 7782-42-5)

Methenamine (CAS 100-97-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4)

Graphite (CAS 7782-42-5)

US. Rhode Island RTK

Carbon black (CAS 1333-86-4)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-May-2016

Revision date 24-May-2017

Version # 02

Further information Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

NFPA ratings



Disclaimer

GRAFTECH INTERNATIONAL HOLDINGS INC. ADVISES THE USERS OF THIS PRODUCT TO STUDY THIS SAFETY DATA SHEET (SDS) AND BECOME AWARE OF PRODUCT HAZARDS AND SAFETY INFORMATION. TO PROMOTE SAFE USE OF THIS PRODUCT, USERS SHOULD NOTIFY THEIR EMPLOYEES, AGENTS AND CONTRACTORS OF THE INFORMATION ON THIS SDS AND ANY PRODUCT HAZARDS AND SAFETY INFORMATION.

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.